

# Black Out Cover

- The cover cuts out all light and is for use in light sensitive areas.
- The Black Out Cover is designed to fit over existing BFM® connectors.
- It is attached using a butterfly mechanism at the top and the base of the cover. This makes installing and removal easy and no tools are required.



VIBRATION



OSCILLATION



COMPRESSION



DUST TIGHT



FOOD SAFETY



ATEX



## PHYSICAL PROPERTIES:

Fibre	Polyester
Colour	Black
Construction/Finish	Triple weave
Weight +/- 10%	220 g/m <sup>2</sup> 6.49 oz/yd <sup>2</sup>
Min. Operating Temp	-70°C / -94°F
Max. Operating Temp*	95°C / 203°F
Max. Surge Temp*	100°C / 212°F

\*(NB: Limited to max. operating temperature of inner connector)

## AVAILABLE SIZES: (in 50mm / 2" increments)

Diameter (also available in 125mm/5")	Ø100mm - 1,650mm (Ø4" - 65")
Length	80mm, 100mm- 1,000mm (3", 4" - 39½")

(Size range is in mm, so inch conversions are approximate only. Restrictions apply for larger diameters. Refer to [Connector Sizes](#) for more information)

## COMPLIANCE:

Complies with the following regulations:  
FDA 21 CFR 177.1520.